

LED OUTLINE LIGHT



Light Output Ratio:	100.0%
Luminaire Power:	3.488 W
90% Beam Spread	56.1V x 59.6H
50% Beam Lumens	696.5 lumens per klm.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 23DEG
Operators: WEIQI
Test Date: 2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity: 56%
Test Distance: 10.580m [K=1.0000]
Remarks:

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		269.1 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	187.2V x 180.0H
	At 50% of Imax	126.8V x 125.4H
	At 90% of Imax	56.1V x 59.6H
Beam Flux	Total	1000.0 lumens per klm.
	To 10% of Imax	978.0 lumens per klm.
	To 50% of Imax	696.5 lumens per klm.
	To 90% of Imax	204.6 lumens per klm.
	Upward LOR	4.2 %
	Downward LOR	95.8 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.13V I:0.0358A P:3.4883W PF:0.4430 Freq:49.99Hz Lamp Flux:205.579x1 lm		
NAME: TL-OU-3110 6W 10X60D	TYPE:	SERIAL No.:
	SUR.:	



DATA OF LAMP		Eff:58.93lm/W	
MODEL		Imax(cd)	55.31
NOMINAL POWER(W)	3	AVAILABILITY(%)	97.8
RATED VOLTAGE(V)	220	Avai. FLUX(lm)	201.0
NOMINAL FLUX(lm)	205.579	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	205.6
TEST VOLTAGE(V)	220.105	q @50%(H,V)	125,127DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		F t	F a
	0.03	0.09	0.16	0.23	0.30	0.36	0.40	0.41	0.37	0.36	0.38	0.37	0.34	0.28	0.22	0.16	0.10	0.03	4.60	4.60
90	0.03	0.11	0.19	0.29	0.38	0.47	0.53	0.58	0.60	0.60	0.57	0.52	0.45	0.36	0.28	0.19	0.11	0.03	6.29	6.29
80	0.03	0.12	0.22	0.34	0.46	0.58	0.68	0.75	0.78	0.78	0.74	0.66	0.56	0.45	0.33	0.22	0.12	0.03	7.85	7.85
70	0.04	0.13	0.25	0.39	0.54	0.70	0.83	0.93	0.98	0.98	0.92	0.82	0.68	0.53	0.38	0.25	0.13	0.04	9.52	9.52
60	0.04	0.14	0.27	0.44	0.63	0.83	1.00	1.13	1.19	1.19	1.11	0.98	0.81	0.62	0.43	0.27	0.14	0.04	11.3	11.3
50	0.04	0.15	0.30	0.49	0.72	0.96	1.16	1.31	1.38	1.37	1.28	1.13	0.92	0.70	0.48	0.29	0.15	0.04	12.9	12.9
40	0.04	0.15	0.32	0.53	0.80	1.07	1.30	1.45	1.52	1.51	1.41	1.24	1.02	0.77	0.52	0.31	0.15	0.04	14.1	14.1
30	0.04	0.16	0.33	0.57	0.86	1.15	1.39	1.54	1.61	1.59	1.50	1.33	1.09	0.82	0.55	0.33	0.16	0.04	15.0	15.0
	0.04	0.16	0.34	0.59	0.89	1.19	1.43	1.59	1.66	1.64	1.55	1.37	1.13	0.85	0.57	0.34	0.16	0.04	15.5	15.5
	0.04	0.16	0.34	0.59	0.89	1.19	1.43	1.58	1.66	1.66	1.57	1.39	1.14	0.86	0.58	0.34	0.16	0.04	15.6	15.6
	0.04	0.16	0.33	0.57	0.86	1.15	1.39	1.55	1.63	1.62	1.53	1.36	1.12	0.84	0.56	0.33	0.16	0.04	15.2	15.2
	0.04	0.15	0.32	0.54	0.81	1.08	1.32	1.48	1.56	1.55	1.46	1.29	1.05	0.79	0.54	0.32	0.15	0.04	14.5	14.5
-30	0.04	0.15	0.30	0.50	0.73	0.98	1.20	1.35	1.43	1.42	1.33	1.17	0.96	0.72	0.50	0.30	0.15	0.04	13.3	13.3
-40	0.04	0.14	0.28	0.45	0.65	0.85	1.04	1.18	1.25	1.25	1.17	1.03	0.85	0.65	0.45	0.28	0.14	0.04	11.7	11.7
-50	0.04	0.13	0.25	0.40	0.56	0.73	0.87	0.98	1.04	1.04	0.98	0.87	0.72	0.56	0.40	0.26	0.13	0.04	9.99	9.99
-60	0.03	0.12	0.23	0.35	0.48	0.60	0.71	0.79	0.83	0.83	0.79	0.71	0.60	0.48	0.35	0.23	0.12	0.04	8.26	8.26
-70	0.03	0.11	0.20	0.30	0.39	0.48	0.56	0.61	0.63	0.63	0.61	0.55	0.48	0.39	0.29	0.20	0.11	0.03	6.61	6.61
-80	0.03	0.10	0.17	0.24	0.31	0.37	0.40	0.40	0.38	0.39	0.42	0.40	0.36	0.30	0.24	0.17	0.10	0.03	4.78	4.78
-90	0.03	0.10	0.17	0.24	0.31	0.37	0.40	0.40	0.38	0.39	0.42	0.40	0.36	0.30	0.24	0.17	0.10	0.03	4.78	4.78
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
F t	0.65	2.40	4.80	7.80	11.3	14.7	17.6	19.6	20.5	20.4	19.3	17.2	14.3	11.0	7.68	4.78	2.42	0.66	197	---
F a	0.65	2.40	4.80	7.80	11.3	14.7	17.6	19.6	20.5	20.4	19.3	17.2	14.3	11.0	7.68	4.78	2.42	0.66	---	197

one-half-peak spread: U:61.0,D:62.6 , L:60.2,R:66.0


NEMA Beam Type: Type 7

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.13V I:0.0358A P:3.4883W PF:0.4430 Freq:49.99Hz Lamp Flux:205.579x1 lm		
NAME: TL-OU-3110 6W 10X60D	TYPE:	SERIAL No.:
	SUR.:	




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.13V I:0.0358A P:3.4883W PF:0.4430 Freq:49.99Hz Lamp Flux:205.579x1 lm		
NAME: TL-OU-3110 6W 10X60D	TYPE:	SERIAL No.:
	SUR.:	



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 23DEG
Operators: WEIQI
Test Date: 2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity: 56%
Test Distance: 10.580m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 23DEG
 Operators: WEIQI
 Test Date: 2017-12-22

g Range: 0 - 120DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.402
 Humidity: 56%
 Test Distance: 10.580m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.13V I:0.0358A P:3.4883W PF:0.4430 Freq:49.99Hz Lamp Flux:205.579x1 lm		
NAME: TL-OU-3110 6W 10X60D	TYPE:	SERIAL No.:
	SUR.:	

Flux out:142.4 lm



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 23DEG
Operators: WEIQI
Test Date: 2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity: 56%
Test Distance: 10.580m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.13V I:0.0358A P:3.4883W PF:0.4430 Freq:49.99Hz Lamp Flux:205.579x1 lm		
NAME: TL-OU-3110 6W 10X60D	TYPE:	SERIAL No.:
	SUR.:	

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	11.0	4.95	2.59	1.32	2.40	1.17	0.93	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	11.0	5.03	2.77	1.40	2.36	1.25	0.89	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-160	11.0	5.22	3.10	1.48	2.26	1.49	0.95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-150	11.0	5.50	3.51	1.90	1.91	2.01	1.11	0.69	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-140	11.0	5.92	3.93	2.54	1.74	2.33	1.64	0.99	0.64	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	11.0	6.54	4.47	3.57	2.30	1.91	2.32	1.71	1.05	0.64	0.49	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	11.0	7.40	5.22	4.37	3.55	2.28	1.87	2.21	1.55	0.79	0.40	0.40	0.41	0.43	0.44	0.44	0.45	0.46	0.46
-110	11.0	8.47	6.35	5.33	4.67	4.18	3.18	2.00	1.49	1.34	0.98	0.67	0.54	0.56	0.76	1.04	1.80	2.64	3.46
-100	11.0	9.71	8.46	7.27	6.28	5.69	5.30	4.40	3.26	1.88	2.14	2.58	3.00	2.26	1.55	0.91	1.32	1.84	2.40
-90	11.0	11.1	11.1	11.2	11.3	11.4	11.5	11.7	11.8	11.9	11.9	12.0	12.0	11.4	10.9	10.4	9.42	8.49	7.55
-80	11.0	11.7	12.3	12.9	13.5	14.2	14.8	15.4	15.9	16.4	16.8	17.1	17.3	17.4	17.4	17.5	17.5	17.5	17.4
-70	11.0	12.2	13.3	14.4	15.5	16.5	17.6	18.5	19.4	20.3	21.0	21.7	22.3	22.9	23.3	23.7	23.9	24.0	24.1
-60	11.0	12.7	14.2	15.7	17.2	18.7	20.1	21.4	22.8	24.1	25.4	26.5	27.6	28.5	29.3	30.1	30.5	30.8	30.9
-50	11.0	13.1	15.0	16.9	18.8	20.6	22.4	24.3	26.2	28.1	30.0	31.7	33.2	34.7	35.9	36.8	37.5	37.9	38.1
-40	11.0	13.4	15.7	17.9	20.1	22.3	24.7	27.1	29.6	32.1	34.6	36.9	38.9	40.7	42.2	43.3	44.1	44.5	44.6
-30	11.0	13.7	16.2	18.8	21.2	23.9	26.6	29.6	32.7	35.8	38.8	41.5	43.9	45.9	47.4	48.5	49.3	49.7	49.7
-20	11.0	13.9	16.6	19.4	22.1	25.1	28.3	31.7	35.2	38.8	42.1	45.1	47.5	49.5	51.0	51.9	52.6	52.9	52.9
-10	11.0	14.1	16.9	19.7	22.7	25.9	29.3	33.1	37.0	40.8	44.3	47.3	49.6	51.4	52.7	53.6	54.2	54.5	54.5
0	11.0	14.1	16.9	19.8	22.9	26.2	29.7	33.6	37.7	41.7	45.3	48.4	50.8	52.6	53.8	54.6	55.1	55.3	55.3
10	11.0	14.0	16.9	19.7	22.6	25.8	29.3	33.0	36.9	40.7	44.3	47.3	49.7	51.5	52.7	53.5	54.0	54.1	54.0
20	11.0	13.9	16.6	19.3	22.0	25.0	28.1	31.5	35.0	38.5	41.8	44.7	47.1	49.0	50.3	51.2	51.7	51.9	51.8
30	11.0	13.7	16.2	18.7	21.1	23.7	26.4	29.3	32.3	35.3	38.2	40.8	43.0	44.8	46.3	47.2	47.9	48.2	48.1
40	11.0	13.4	15.6	17.8	19.9	22.1	24.4	26.7	29.1	31.4	33.7	35.8	37.7	39.3	40.6	41.6	42.3	42.7	42.7
50	11.0	13.0	14.9	16.7	18.5	20.3	22.1	23.9	25.6	27.3	29.0	30.5	31.9	33.2	34.2	35.0	35.6	36.0	36.1
60	11.0	12.6	14.1	15.5	17.0	18.4	19.7	21.0	22.1	23.3	24.4	25.5	26.4	27.2	27.9	28.4	28.8	29.1	29.1
70	11.0	12.2	13.2	14.2	15.2	16.2	17.2	18.1	18.8	19.5	20.2	20.8	21.4	21.9	22.2	22.5	22.7	22.7	22.7
80	11.0	11.7	12.2	12.7	13.4	14.0	14.5	15.0	15.5	15.9	16.2	16.5	16.8	17.0	17.1	17.2	17.1	17.0	16.9
90	11.0	11.0	11.0	11.0	11.2	11.3	11.5	11.5	11.6	11.6	11.7	11.7	11.7	11.6	11.4	11.2	9.57	7.97	6.37
100	11.0	9.67	8.41	7.25	6.35	5.77	5.42	4.29	2.99	1.58	1.52	1.50	1.44	1.14	0.99	0.88	0.94	1.05	1.20
110	11.0	8.45	6.36	5.33	4.70	4.28	3.36	2.21	1.72	1.64	1.26	0.93	0.77	0.67	0.72	0.84	1.53	2.33	3.12
120	11.0	7.39	5.21	4.38	3.64	2.43	1.97	2.23	1.77	1.00	0.55	0.51	0.50	0.51	0.51	0.51	0.52	0.53	0.53
130	11.0	6.54	4.48	3.61	2.39	1.98	2.48	1.95	1.27	0.78	0.59	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	11.0	5.92	3.93	2.59	1.84	2.42	1.68	1.08	0.77	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	11.0	5.50	3.52	1.94	1.96	2.02	1.00	0.72	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	11.0	5.22	3.11	1.52	2.30	1.41	0.87	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	11.0	5.03	2.78	1.42	2.38	1.20	0.86	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	11.0	4.95	2.59	1.32	2.40	1.17	0.93	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.13V I:0.0358A P:3.4883W PF:0.4430 Freq:49.99Hz Lamp Flux:205.579x1 lm		
NAME: TL-OU-3110 6W 10X60D	TYPE:	SERIAL No.:
	SUR.:	

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.51	1.03	2.39	1.21	2.61	5.30	11.5	
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	0.98	2.37	1.31	2.83	5.40	11.5	
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.49	1.18	2.32	1.42	3.20	5.61	11.5	
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.53	0.52	1.89	1.95	1.99	3.66	5.94	11.5	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.61	0.46	1.45	2.39	1.73	2.74	4.14	6.42	11.5	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.51	0.46	0.56	1.79	2.43	1.91	2.51	3.79	4.76	7.11	11.5	
-120	0.46	0.46	0.46	0.45	0.44	0.43	0.43	0.41	0.83	1.64	2.24	1.86	2.50	3.84	4.63	5.59	8.07	11.5	
-110	2.57	1.67	0.88	0.68	0.57	0.60	0.73	1.09	1.52	1.61	2.20	3.45	4.38	4.94	5.71	6.92	9.19	11.5	
-100	1.90	1.45	1.10	1.69	2.36	3.06	2.58	2.04	1.63	3.12	4.44	5.54	6.04	6.80	7.95	9.18	10.4	11.5	
-90	8.66	9.76	10.9	11.2	11.6	11.9	11.9	11.9	11.9	11.8	11.8	11.7	11.7	11.7	11.7	11.6	11.6	11.5	
-80	17.6	17.8	17.9	17.7	17.4	17.2	16.9	16.6	16.2	15.7	15.2	14.7	14.2	13.7	13.2	12.7	12.1	11.5	
-70	24.0	23.9	23.7	23.3	22.8	22.2	21.6	20.9	20.1	19.3	18.4	17.5	16.6	15.6	14.6	13.6	12.6	11.5	
-60	30.8	30.5	30.0	29.3	28.4	27.5	26.5	25.3	24.1	22.8	21.4	20.1	18.8	17.4	15.9	14.5	13.0	11.5	
-50	37.8	37.4	36.6	35.6	34.4	33.0	31.5	29.8	28.1	26.2	24.4	22.5	20.7	19.0	17.1	15.2	13.4	11.5	
-40	44.4	43.8	42.8	41.6	40.1	38.3	36.4	34.2	31.9	29.5	27.2	24.8	22.5	20.3	18.1	15.9	13.7	11.5	
-30	49.4	48.8	47.8	46.5	44.9	42.9	40.6	38.0	35.3	32.4	29.6	26.8	24.1	21.4	18.9	16.4	14.0	11.5	
-20	52.7	52.1	51.2	49.9	48.2	46.2	43.7	40.9	37.9	34.7	31.5	28.3	25.2	22.3	19.5	16.8	14.2	11.5	
-10	54.3	53.9	53.0	51.8	50.2	48.1	45.6	42.7	39.5	36.0	32.6	29.2	25.9	22.8	19.8	17.0	14.3	11.5	
0	55.0	54.4	53.5	52.3	50.6	48.6	46.1	43.1	39.9	36.4	32.9	29.4	26.1	22.9	19.9	17.1	14.3	11.5	
10	53.6	52.9	52.0	50.7	49.1	47.1	44.6	41.9	38.8	35.5	32.1	28.8	25.6	22.6	19.7	17.0	14.3	11.5	
20	51.4	50.8	49.8	48.5	46.9	44.9	42.5	39.7	36.8	33.7	30.7	27.7	24.7	21.9	19.3	16.7	14.1	11.5	
30	47.8	47.1	46.2	44.9	43.2	41.3	39.1	36.7	34.1	31.4	28.7	26.0	23.4	21.0	18.6	16.2	13.9	11.5	
40	42.4	41.8	40.9	39.8	38.4	36.7	34.8	32.8	30.6	28.4	26.2	24.0	21.8	19.8	17.7	15.7	13.6	11.5	
50	35.8	35.4	34.7	33.8	32.7	31.4	29.9	28.4	26.8	25.1	23.4	21.7	20.0	18.3	16.7	15.0	13.3	11.5	
60	29.0	28.7	28.2	27.6	26.8	25.9	24.9	23.9	22.8	21.6	20.4	19.2	18.0	16.8	15.4	14.2	12.9	11.5	
70	22.6	22.4	22.1	21.8	21.3	20.8	20.1	19.5	18.8	18.2	17.5	16.8	15.9	15.0	14.2	13.3	12.5	11.5	
80	16.9	16.8	16.7	16.4	16.2	15.9	15.7	15.4	15.0	14.8	14.4	14.1	13.7	13.3	12.8	12.4	12.0	11.5	
90	7.49	8.61	9.73	10.2	10.8	11.3	11.0	10.7	10.4	10.7	11.0	11.3	11.3	11.3	11.4	11.4	11.5	11.5	
100	0.96	0.75	0.58	0.83	1.16	1.64	1.48	1.13	0.68	2.18	3.84	5.50	5.98	6.72	7.79	9.04	10.3	11.5	
110	2.43	1.71	1.06	0.81	0.65	0.66	0.79	1.10	1.50	1.60	2.18	3.40	4.33	4.88	5.62	6.83	9.13	11.5	
120	0.53	0.52	0.51	0.50	0.50	0.48	0.47	0.46	0.88	1.66	2.34	1.91	2.46	3.74	4.58	5.53	8.02	11.5	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.55	0.51	0.56	1.81	2.48	1.97	2.46	3.72	4.72	7.08	11.5	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.62	0.53	1.57	2.51	1.76	2.70	4.11	6.39	11.5	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.57	0.67	2.05	2.02	1.96	3.65	5.92	11.5	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.52	1.31	2.38	1.43	3.18	5.60	11.5	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.51	1.05	2.41	1.31	2.82	5.39	11.5	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.51	1.03	2.39	1.21	2.61	5.30	11.5	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-22

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks: