

LED OUTLINE LIGHT



Light Output Ratio:	100.0%
Luminaire Power:	5.39 W
90% Beam Spread	59.0V x 0.9H
50% Beam Lumens	590.9 lumens per klm.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 23DEG
Operators: WEIQI
Test Date: 2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity: 56%
Test Distance: 10.580m [K=1.0000]
Remarks:

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		2795.1 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	131.9V x 13.2H
	At 50% of Imax	117.6V x 4.7H
	At 90% of Imax	59.0V x 0.9H
Beam Flux	Total	1001.3 lumens per klm.
	To 10% of Imax	712.3 lumens per klm.
	To 50% of Imax	590.9 lumens per klm.
	To 90% of Imax	186.0 lumens per klm.
	Upward LOR	0.3 %
	Downward LOR	99.8 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.07V I:0.0522A P:5.3897W PF:0.4689 Freq:49.99Hz Lamp Flux:127.222x1 lm		
NAME: TL-OU-3220D-1 5W 3000K 2X120D	TYPE:	SERIAL No.:
	SUR.:	



DATA OF LAMP		Eff:23.60lm/W	
MODEL		Imax(cd)	355.6
NOMINAL POWER(W)	5	AVAILABILITY(%)	72.4
RATED VOLTAGE(V)	220	Avai. FLUX(lm)	92.16
NOMINAL FLUX(lm)	127.222	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	127.2
TEST VOLTAGE(V)	220.062	q @50%(H,V)	5,118DEG

AREA FLUX DIAGRAM																	UNIT:lm	F t	F a
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.06	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.08	0.00
70	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.15	1.12	1.12	0.15	0.07	0.03	0.00	0.00	0.00	0.00	2.69	2.18
60	0.00	0.00	0.00	0.00	0.02	0.09	0.19	0.37	3.74	3.75	0.40	0.23	0.12	0.04	0.00	0.00	0.00	8.98	7.64
50	0.00	0.00	0.00	0.01	0.08	0.18	0.31	0.37	4.22	4.27	0.43	0.33	0.20	0.09	0.02	0.00	0.00	10.5	8.42
40	0.00	0.00	0.00	0.04	0.12	0.24	0.37	0.43	4.10	4.20	0.49	0.39	0.26	0.13	0.05	0.00	0.00	10.8	8.08
30	0.00	0.00	0.00	0.06	0.15	0.28	0.42	0.45	3.69	3.89	0.50	0.45	0.29	0.15	0.07	0.00	0.00	10.4	7.09
20	0.00	0.00	0.01	0.08	0.16	0.29	0.46	0.46	3.14	3.59	0.51	0.49	0.31	0.16	0.08	0.01	0.00	9.74	6.28
10	0.00	0.00	0.01	0.08	0.17	0.30	0.47	0.47	3.08	3.63	0.50	0.50	0.32	0.17	0.08	0.02	0.00	9.80	6.17
0	0.00	0.00	0.01	0.08	0.17	0.30	0.47	0.46	3.25	3.49	0.49	0.50	0.31	0.16	0.08	0.02	0.00	9.80	6.24
-10	0.00	0.00	0.01	0.08	0.16	0.30	0.45	0.45	3.41	3.37	0.48	0.48	0.30	0.16	0.07	0.01	0.00	9.72	6.28
-20	0.00	0.00	0.00	0.06	0.15	0.28	0.42	0.43	3.92	3.87	0.45	0.44	0.28	0.14	0.07	0.00	0.00	10.5	7.26
-30	0.00	0.00	0.00	0.04	0.12	0.25	0.37	0.43	4.39	4.35	0.43	0.38	0.24	0.12	0.05	0.00	0.00	11.2	8.52
-40	0.00	0.00	0.00	0.01	0.09	0.19	0.31	0.37	4.33	4.32	0.36	0.31	0.18	0.09	0.02	0.00	0.00	10.6	8.58
-50	0.00	0.00	0.00	0.00	0.03	0.10	0.20	0.37	3.67	3.66	0.36	0.20	0.11	0.04	0.00	0.00	0.00	8.75	7.46
-60	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.16	1.15	1.15	0.16	0.05	0.02	0.00	0.00	0.00	0.00	2.76	1.96
-70	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.06	0.08	0.07	0.05	0.02	0.01	0.00	0.00	0.00	0.00	0.33	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.10	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
HORIZONTAL(DEG)																			
F t	0.00	0.01	0.05	0.55	1.43	2.84	4.57	5.45	47.3	48.8	5.80	4.89	2.97	1.45	0.58	0.07	0.01	0.00	127
F a	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.19	45.0	46.7	0.20	0.00	0.00	0.00	0.00	0.00	0.00	---	92


one-half-peak spread: U:31.4,D:34.9 , L:2.4,R:2.4,NEMA Beam Type: Type 1 x 7 (H x V)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.07V I:0.0522A P:5.3897W PF:0.4689 Freq:49.99Hz Lamp Flux:127.222x1 lm		
NAME: TL-OU-3220D-1 5W 3000K 2X120D	TYPE:	SERIAL No.:
	SUR.:	




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:23DEG
 Operators:WEIQI
 Test Date:2017-12-23

g Range: 0 - 120DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
 Humidity:56%
 Test Distance:10.580m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.07V I:0.0522A P:5.3897W PF:0.4689 Freq:49.99Hz Lamp Flux:127.222x1 lm		
NAME: TL-OU-3220D-1 5W 3000K 2X120D	TYPE:	SERIAL No.
	SUR.:	



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 23DEG
 Operators: WEIQI
 Test Date: 2017-12-23

g Range: 0 - 120DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.402
 Humidity: 56%
 Test Distance: 10.580m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.07V I:0.0522A P:5.3897W PF:0.4689 Freq:49.99Hz Lamp Flux:127.222x1 lm		
NAME: TL-OU-3220D-1 5W 3000K 2X120D	TYPE:	SERIAL No.:
	SUR.:	



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.07V I:0.0522A P:5.3897W PF:0.4689 Freq:49.99Hz Lamp Flux:127.222x1 lm		
NAME: TL-OU-3220D-1 5W 3000K 2X120D	TYPE:	SERIAL No.:
	SUR.:	

Table--1

UNIT: cd

H(DEC) V(DEC)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.01	0.03	0.04	0.05	0.09	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	0.00	0.01	0.03	0.04	0.05	0.07	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-160	0.00	0.01	0.02	0.04	0.04	0.06	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-150	0.00	0.01	0.02	0.03	0.04	0.04	0.07	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-140	0.00	0.01	0.02	0.02	0.04	0.03	0.05	0.07	0.09	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	0.00	0.01	0.01	0.02	0.03	0.04	0.05	0.05	0.09	0.17	0.24	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.01	0.01	0.01	0.02	0.03	0.04	0.05	0.09	0.12	0.18	0.22	0.26	0.29	0.34	0.38	0.42	0.48	0.53
-110	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.03	0.05	0.07	0.10	0.14	0.19	0.23	0.25	0.28	0.34	0.39	0.44
-100	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.03	0.05	0.07	0.09	0.11	0.13	0.15	0.19	0.24	0.29
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.04	0.06	0.08	0.12	0.16	0.20
-80	0.00	0.01	0.00	0.00	0.01	0.03	0.05	0.08	0.12	0.15	0.21	0.32	0.44	0.67	0.91	1.17	1.38	1.58	1.76
-70	0.00	0.01	0.01	0.03	0.07	0.20	0.08	0.01	0.01	0.00	0.19	0.47	0.67	1.14	1.71	2.33	3.25	4.49	5.75
-60	0.00	0.01	0.04	0.11	0.24	0.00	0.00	0.01	0.19	0.07	0.56	1.82	2.33	3.55	5.68	6.90	43.9	106	168
-50	0.00	0.01	0.07	0.26	0.00	0.00	0.19	0.06	0.50	2.85	4.30	5.91	8.06	10.1	10.4	10.1	39.2	134	230
-40	0.00	0.02	0.14	0.08	0.00	0.04	0.02	0.68	3.57	4.91	6.67	8.78	11.0	12.5	13.2	13.6	14.6	147	289
-30	0.00	0.03	0.21	0.00	0.00	0.01	0.13	3.45	4.80	6.34	8.29	10.8	13.5	14.9	14.0	13.4	19.8	127	329
-20	0.00	0.04	0.25	0.00	0.00	0.01	2.13	4.16	5.55	7.26	9.33	11.6	14.1	16.2	15.9	14.2	20.3	62.0	350
-10	0.00	0.05	0.28	0.00	0.00	0.02	3.22	4.57	6.01	7.67	9.63	11.9	14.6	17.2	16.9	14.3	17.8	63.2	354
0	0.00	0.05	0.29	0.00	0.00	0.02	3.37	4.64	6.05	7.67	9.65	12.2	14.8	17.4	17.6	14.8	18.7	54.4	345
10	0.00	0.05	0.28	0.00	0.00	0.02	3.22	4.55	5.97	7.58	9.55	11.9	14.6	17.3	17.5	14.9	18.0	56.9	344
20	0.00	0.04	0.25	0.00	0.01	0.01	2.13	4.13	5.48	7.11	9.10	11.4	14.0	16.3	16.6	14.9	20.0	56.1	327
30	0.00	0.03	0.20	0.00	0.01	0.02	0.11	3.43	4.72	6.21	8.03	10.4	13.0	14.8	14.6	14.3	19.3	119	308
40	0.00	0.02	0.15	0.12	0.00	0.03	0.01	0.48	3.54	4.79	6.40	8.40	10.6	12.5	13.6	13.6	14.0	138	270
50	0.00	0.01	0.07	0.26	0.00	0.01	0.11	0.03	0.34	2.59	4.08	5.55	7.69	9.92	10.4	9.94	39.1	135	232
60	0.00	0.01	0.03	0.12	0.24	0.00	0.00	0.04	0.14	0.05	0.21	1.09	1.71	3.10	5.57	6.73	45.5	110	175
70	0.00	0.01	0.01	0.02	0.07	0.18	0.08	0.00	0.01	0.01	0.05	0.15	0.08	0.08	0.17	0.36	0.55	0.68	0.76
80	0.00	0.01	0.00	0.00	0.01	0.02	0.04	0.06	0.07	0.06	0.10	0.15	0.16	0.24	0.39	0.58	0.67	0.76	0.83
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.04	0.07	0.09	0.11	0.11	0.11	0.10
100	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.03	0.04	0.06	0.08	0.11	0.14	0.15	0.17	0.18	0.18	0.18	0.18
110	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.06	0.08	0.10	0.13	0.18	0.22	0.26	0.27	0.29	0.31	0.30	0.28
120	0.00	0.01	0.01	0.02	0.05	0.04	0.06	0.07	0.11	0.16	0.22	0.26	0.30	0.33	0.34	0.36	0.37	0.35	0.34
130	0.00	0.01	0.02	0.04	0.04	0.06	0.07	0.09	0.12	0.20	0.30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.01	0.03	0.04	0.06	0.07	0.09	0.10	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.01	0.03	0.04	0.06	0.07	0.11	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.01	0.03	0.04	0.06	0.08	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.01	0.03	0.04	0.06	0.09	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.01	0.03	0.04	0.05	0.09	0.12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.07V I:0.0522A P:5.3897W PF:0.4689 Freq:49.99Hz Lamp Flux:127.222x1 lm		
NAME: TL-OU-3220D-1 5W 3000K 2X120D	TYPE:	SERIAL No.:
	SUR.:	

Table--2

UNIT: cd

H(DEC) V(DEC)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.06	0.04	0.02	0.01	0.00	0.00	
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.05	0.03	0.02	0.01	0.00	0.00	
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.04	0.03	0.02	0.01	0.00	0.00	
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.05	0.03	0.03	0.01	0.00	0.00	0.00	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.05	0.04	0.04	0.03	0.02	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.09	0.06	0.04	0.04	0.04	0.01	0.02	0.00	0.00	0.00	
-120	0.47	0.41	0.35	0.31	0.26	0.21	0.16	0.11	0.07	0.05	0.04	0.03	0.02	0.02	0.01	0.00	0.00	0.00	
-110	0.38	0.32	0.25	0.22	0.18	0.14	0.10	0.06	0.03	0.02	0.02	0.02	0.01	0.00	0.00	0.00	0.00	0.00	
-100	0.24	0.19	0.14	0.12	0.09	0.07	0.04	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.16	0.12	0.07	0.05	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	1.50	1.23	0.95	0.75	0.56	0.39	0.28	0.20	0.14	0.11	0.08	0.04	0.02	0.01	0.01	0.00	0.00	0.00	
-70	4.33	2.95	1.94	1.37	0.84	0.46	0.36	0.18	0.01	0.01	0.00	0.07	0.20	0.08	0.04	0.01	0.00	0.00	
-60	106	43.8	6.89	6.18	4.96	3.07	2.24	1.38	0.11	0.19	0.01	0.00	0.00	0.27	0.10	0.04	0.00	0.00	
-50	134	38.5	9.66	10.4	10.1	7.82	5.65	4.15	3.14	1.00	0.02	0.18	0.00	0.00	0.29	0.07	0.01	0.00	
-40	146	12.9	13.2	13.9	12.8	10.7	8.40	6.35	4.69	3.48	1.91	0.02	0.04	0.00	0.02	0.14	0.02	0.00	
-30	125	18.4	14.2	15.1	15.4	13.3	10.4	7.87	6.04	4.56	3.39	0.86	0.02	0.00	0.00	0.21	0.03	0.00	
-20	59.0	19.9	15.2	17.6	17.1	14.3	11.4	8.97	6.94	5.28	3.98	2.86	0.02	0.00	0.00	0.26	0.04	0.00	
-10	64.2	18.5	15.5	18.5	18.3	15.4	12.2	9.43	7.41	5.77	4.36	3.17	0.23	0.00	0.00	0.29	0.05	0.00	
0	55.2	19.4	15.9	19.0	18.6	15.7	12.5	9.56	7.49	5.84	4.44	3.24	0.44	0.00	0.00	0.29	0.05	0.00	
10	77.7	20.5	16.0	18.4	18.4	15.8	12.4	9.57	7.54	5.86	4.42	3.19	0.23	0.01	0.00	0.28	0.05	0.00	
20	72.1	24.5	16.1	17.2	17.3	15.2	12.0	9.37	7.22	5.46	4.07	2.89	0.03	0.01	0.00	0.26	0.04	0.00	
30	125	24.7	15.1	15.0	15.9	14.2	11.3	8.45	6.43	4.81	3.49	0.87	0.03	0.00	0.00	0.22	0.03	0.00	
40	140	18.3	15.7	14.0	13.3	11.8	9.33	6.97	5.05	3.67	2.11	0.04	0.06	0.00	0.02	0.15	0.02	0.00	
50	136	41.1	11.7	11.6	11.0	8.77	6.30	4.45	3.32	1.45	0.01	0.28	0.00	0.00	0.26	0.07	0.01	0.00	
60	110	46.0	7.38	6.78	5.86	4.42	2.97	1.82	0.27	0.29	0.10	0.00	0.01	0.23	0.12	0.03	0.00	0.00	
70	0.69	0.56	0.41	0.39	0.33	0.14	0.04	0.04	0.01	0.01	0.01	0.06	0.20	0.08	0.03	0.01	0.00	0.00	
80	0.78	0.71	0.64	0.53	0.42	0.32	0.22	0.15	0.15	0.13	0.09	0.06	0.02	0.01	0.01	0.00	0.00	0.00	
90	0.10	0.10	0.10	0.08	0.07	0.05	0.04	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.18	0.18	0.18	0.16	0.14	0.12	0.10	0.08	0.06	0.04	0.03	0.01	0.01	0.00	0.00	0.00	0.00	0.00	
110	0.29	0.29	0.27	0.24	0.22	0.20	0.18	0.16	0.12	0.08	0.05	0.03	0.02	0.02	0.00	0.00	0.00	0.00	
120	0.35	0.36	0.35	0.33	0.31	0.27	0.24	0.21	0.16	0.11	0.06	0.04	0.04	0.04	0.02	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.23	0.16	0.10	0.07	0.05	0.04	0.04	0.03	0.01	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.09	0.07	0.05	0.03	0.02	0.01	0.00	0.00	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.12	0.08	0.05	0.04	0.03	0.01	0.00	0.00	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.06	0.04	0.03	0.01	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.06	0.04	0.02	0.01	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.06	0.04	0.02	0.01	0.00	0.00	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:23DEG
Operators:WEIQI
Test Date:2017-12-23

g Range: 0 - 120DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.402
Humidity:56%
Test Distance:10.580m [K=1.0000]
Remarks: