



STREETLIGHT PHOTOMETRIC TEST REPORT

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 95lm	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 95.43 lm/W			
MODEMYCP-LED2009-24-T2-830		Imax(cd)	2090	η street_up(%)	6.3
NOMINAL POWER(W)	23	LOR(%)	100.0	η street_down(%)	44.4
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	2257	η house_up(%)	6.3
NOMINAL FLUX(lm)	2257.06	MAXIMUM @ (C, γ)	110,59.0	η house_down(%)	43.0
LAMPS INSIDE	1	η up(%)	12.6	76 FLASHAREA(m2)	0.02500
TEST VOLTAGE(V)	220	η down(%)	87.4	SLI	18.815




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 95lm	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:



Classification:



IES:Type V - Very Short
 CIE:Broad - Short
 IES:Semi cut-off
 CIE:Semi-cut-off
 Max.At80:51.54cd/klm
 Max.At90:27.17cd/klm
 Max.80-90:51.54cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
I _{max} =100%	2090
90%	1881
80%	1672
70%	1463
60%	1254
50%	1045
40%	836
30%	627
20%	418
10%	209
5%	105

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:20DEG
 Operators:JOE
 Test Date:2021-09-09

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
 Humidity:45%
 Test Distance:8.040m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 20DEG
Operators: JOE
Test Date: 2021-09-09

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity: 45%
Test Distance: 8.040m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 951m	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	23.39	26.76	28.54	25.60	27.66	27.69	25.10	23.67	0- 10	0.9863	0.9863	0.04,0.04
20	83.85	93.91	128.9	117.8	129.0	129.5	112.4	86.00	10- 20	19.40	20.39	0.90,0.90
30	154.9	166.6	237.9	317.1	297.5	290.9	202.4	155.0	20- 30	78.28	98.67	4.37,4.37
40	304.7	267.7	488.4	469.6	488.3	574.8	409.2	276.0	30- 40	202.3	301.0	13.3,13.3
50	359.8	277.6	1231	1212	1172	1102	439.3	306.8	40- 50	454.4	755.4	33.5,33.5
60	282.3	177.2	1317	582.0	316.4	1630	179.1	222.5	50- 60	667.8	1423	63.1,63.1
70	159.1	123.3	198.3	162.0	132.0	314.6	119.5	138.1	60- 70	341.9	1765	78.2,78.2
80	91.32	82.46	92.00	91.56	84.17	103.9	80.83	86.39	70- 80	131.1	1896	84.84
90	58.04	58.57	60.77	58.91	58.09	60.92	58.99	57.52	80- 90	77.24	1973	87.4,87.4
100	57.86	60.18	60.24	59.08	58.90	60.23	60.26	57.70	90-100	64.83	2038	90.3,90.3
110	52.22	55.71	56.26	56.70	57.13	56.57	56.19	52.57	100-110	60.97	2099	93,93
120	45.77	49.84	51.12	52.61	53.60	52.43	51.25	46.80	110-120	52.49	2152	95.3,95.3
130	39.86	43.30	44.99	46.88	48.20	47.03	45.40	40.80	120-130	42.78	2195	97.2,97.2
140	31.17	34.55	36.36	38.29	39.69	38.63	36.65	32.47	130-140	31.49	2226	98.6,98.6
150	21.41	23.28	25.28	26.82	28.05	27.41	25.35	22.17	140-150	19.38	2245	99.5,99.5
160	11.16	11.86	13.36	14.46	15.17	15.05	13.37	11.41	150-160	8.985	2254	99.9,99.9
170	3.359	3.378	3.679	4.119	4.243	4.319	3.990	3.378	160-170	2.466	2257	100,100
180	0.7408	0.7181	0.7181	0.7030	0.7332	0.7200	0.7181	0.7087	170-180	0.2078	2257	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 951m	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 20DEG
 Operators: JOE
 Test Date: 2021-09-09

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.366
 Humidity: 45%
 Test Distance: 8.040m [K=1.0000]
 Remarks:

LCS REPORT

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 95lm	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

BUG REPORT

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 951m	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	49.644	2.2
FM - Front-Medium(30-60)	672.3	29.8
FH - Front-High(60-80)	242.43	10.7
FVH - Front-Very High(80-90)	38.587	1.7
Total Forward Light	1145.1	50.7

BL - Back-Low(0-30)	49.026	2.2
BM - Back-Medium(30-60)	652.25	28.9
BH - Back-High(60-80)	230.57	10.2
BVH - Back-Very High(80-90)	38.653	1.7
Total Back Light	1111.9	49.3

UL - Uplight-Low(90-100)	64.831	2.9
UH - Uplight-High(100-180)	218.76	9.7
Total Up Light	283.59	12.6

BUG(Back,Up,Glare) Rating	B1-U3-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	970.5	141.43	1111.9
Street Side	1003	142.16	1145.1


C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 95lm	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 951m	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	0.33	0.33	0.31	0.31	0.30	0.30	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.30	0.30	0.31	0.30	0.31	0.33
5	3.23	3.19	3.49	3.37	3.73	3.41	3.65	3.37	3.58	3.33	3.49	3.20	3.33	3.06	3.14	2.84	2.90	2.62	3.14
10	23.4	22.6	26.1	24.7	28.3	25.2	27.1	26.7	28.1	28.5	32.9	28.6	33.9	27.0	24.2	25.1	22.6	21.8	27.7
15	55.6	53.6	59.5	60.6	63.2	65.1	65.2	65.7	66.1	67.8	68.1	66.9	74.9	60.2	63.0	67.5	53.9	61.7	68.6
20	83.8	79.8	84.5	92.7	90.8	97.0	106	101	113	129	115	119	124	118	117	121	118	118	129
25	111	110	117	110	121	139	141	157	177	161	173	192	188	204	208	202	216	210	227
30	155	150	148	139	152	181	183	211	247	238	271	323	340	331	303	274	275	279	298
35	222	208	196	173	189	230	273	314	352	345	417	510	443	362	342	329	357	336	345
40	305	295	250	217	234	301	410	482	510	488	523	577	507	472	467	449	497	468	488
45	362	341	296	247	256	364	574	766	852	754	657	666	653	685	774	709	746	706	821
50	360	326	295	240	241	314	519	893	1295	1231	947	935	1083	1192	1233	1036	983	972	1172
55	328	284	265	216	212	228	322	595	1235	1754	1575	1643	1673	1284	959	696	576	589	799
60	282	243	224	187	181	174	190	273	620	1317	1772	2062	1439	753	411	291	251	254	316
65	222	192	176	156	152	143	144	162	238	525	947	1251	749	332	205	174	164	166	180
70	159	147	136	129	126	120	119	125	146	198	328	488	322	182	142	129	125	127	132
75	119	115	107	106	105	99.9	98.3	102	108	124	154	196	166	127	110	104	102	103	105
80	91.3	88.5	85.1	84.6	83.5	81.5	79.8	82.2	84.9	92.0	103	116	108	95.8	87.3	83.9	82.9	84.1	84.2
85	68.1	68.4	66.6	66.2	66.0	65.7	64.7	66.5	68.0	70.8	74.5	78.8	76.3	72.8	69.3	69.6	67.0	67.9	68.3
90	58.0	58.1	58.3	58.6	58.6	58.5	58.7	59.3	60.0	60.8	61.3	61.3	60.4	59.4	58.4	57.8	57.4	57.5	58.1
95	58.6	58.8	59.3	59.8	60.0	59.9	59.8	60.0	60.3	60.9	61.2	61.1	60.4	59.6	58.9	58.4	58.2	58.2	58.8
100	57.9	58.5	59.1	59.8	60.1	60.2	60.0	60.0	60.0	60.2	60.4	60.3	59.8	59.3	58.8	58.5	58.4	58.4	58.9
105	55.6	56.5	57.2	58.0	58.4	58.9	58.8	58.7	58.5	58.6	58.7	58.8	58.5	58.4	58.1	57.9	57.9	57.9	58.3
110	52.2	53.2	53.9	54.9	55.4	56.0	56.1	56.3	56.1	56.3	56.3	56.6	56.6	56.8	56.6	56.8	56.7	56.8	57.1
115	48.7	49.7	50.5	51.5	52.2	52.9	53.2	53.5	53.5	53.7	53.8	54.2	54.4	54.8	54.8	55.1	55.2	55.3	55.6
120	45.8	46.7	47.6	48.6	49.5	50.2	50.4	50.7	50.8	51.1	51.3	51.7	52.0	52.5	52.7	53.1	53.3	53.4	53.6
125	43.0	43.8	44.6	45.6	46.5	47.3	47.6	47.8	47.9	48.3	48.4	49.0	49.3	49.9	50.2	50.6	50.8	51.1	51.2
130	39.9	40.4	41.0	42.0	42.8	43.8	44.2	44.6	44.6	45.0	45.2	45.8	46.1	46.7	47.0	47.6	47.8	48.1	48.2
135	35.9	36.4	37.0	38.0	38.8	39.7	40.1	40.6	40.7	41.2	41.4	42.0	42.3	42.9	43.3	43.9	44.1	44.5	44.5
140	31.2	31.8	32.5	33.6	34.2	34.9	35.2	35.7	35.9	36.4	36.6	37.2	37.4	38.1	38.5	39.1	39.4	39.8	39.7
145	26.4	27.0	27.6	28.5	29.0	29.5	29.6	30.2	30.4	31.0	31.2	31.8	32.0	32.6	32.9	33.5	33.8	34.2	34.1
150	21.4	21.8	22.0	22.7	23.0	23.6	23.8	24.4	24.7	25.3	25.5	26.0	26.1	26.7	26.9	27.5	27.7	28.2	28.0
155	16.2	16.4	16.4	16.8	17.0	17.6	17.9	18.5	18.8	19.3	19.5	20.0	20.1	20.6	20.7	21.2	21.4	21.9	21.7
160	11.2	11.3	11.3	11.6	11.7	12.1	12.3	12.7	12.9	13.4	13.5	13.9	14.0	14.4	14.5	14.9	15.1	15.5	15.2
165	6.82	6.94	6.82	7.02	7.00	7.28	7.33	7.63	7.69	7.98	8.06	8.35	8.42	8.73	8.80	9.12	9.21	9.52	9.21
170	3.36	3.40	3.29	3.38	3.31	3.45	3.39	3.55	3.50	3.68	3.66	3.88	3.87	4.12	4.12	4.37	4.34	4.58	4.24
175	1.36	1.31	1.28	1.26	1.27	1.26	1.27	1.27	1.29	1.31	1.33	1.36	1.38	1.43	1.46	1.52	1.56	1.61	1.43
180	0.74	0.73	0.73	0.72	0.72	0.72	0.72	0.71	0.72	0.72	0.71	0.71	0.70	0.70	0.70	0.71	0.72	0.76	0.73

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.62V I:0.1096A P:23.653W PF:0.9823 Freq:49.99Hz Lamp Flux:2257.06x1 lm		
NAME: TL-OU-KLEIO-24-T2-830 951m	TYPE:BOLLARD LIGHT	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: T-LUCE	SUR.:0.3M*0.3M	Shielding Angle:

Table--2

UNIT: cd

C (DEG) γ (DEG)	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350		
0	0.33	0.31	0.31	0.30	0.30	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.30	0.30	0.31	0.30	0.31		
5	3.16	2.85	2.90	2.66	2.71	2.50	2.54	2.37	2.43	2.29	2.44	2.44	2.74	2.77	3.15	3.15	3.79		
10	29.0	24.1	25.4	25.4	30.0	28.5	30.0	22.4	25.1	26.1	26.0	23.1	23.3	24.1	23.3	23.8	26.2		
15	68.2	67.3	62.7	64.1	58.0	65.3	62.4	56.5	63.4	60.3	59.9	53.4	57.5	54.7	55.9	54.1	56.9		
20	130	128	115	133	126	124	118	111	112	99.1	95.4	88.3	85.7	86.3	85.9	81.4	83.7		
25	226	217	200	194	192	173	178	160	147	139	126	113	115	119	116	119	122		
30	328	357	348	302	280	264	240	233	202	173	162	145	146	164	165	169	173		
35	376	435	520	448	422	394	353	338	293	226	198	181	194	232	245	254	254		
40	494	516	580	572	577	588	567	528	409	305	231	225	254	298	328	346	341		
45	794	726	712	680	822	940	887	800	515	341	252	242	286	343	372	382	388		
50	1244	1287	1121	982	1222	1415	1154	770	439	288	240	236	293	320	365	360	371		
55	990	1433	1878	1622	1703	1603	867	451	267	216	219	217	257	275	338	330	338		
60	447	913	1687	1804	1456	969	407	240	179	171	180	186	211	234	281	297	300		
65	222	409	869	983	650	362	200	163	143	142	148	152	166	184	213	227	229		
70	150	206	343	375	254	177	139	127	119	121	126	127	133	143	153	159	159		
75	114	135	169	171	143	120	107	103	99.3	101	106	106	106	114	118	119	119		
80	89.0	98.7	109	108	99.7	90.5	84.8	82.9	80.8	82.5	84.4	85.1	84.7	88.1	91.1	90.3	89.3		
85	70.1	73.7	76.4	76.9	74.1	70.6	68.5	67.0	65.7	66.9	67.0	67.0	66.5	68.2	67.5	67.6	66.9		
90	58.8	59.6	60.5	60.9	60.9	60.4	59.9	59.3	59.0	58.8	58.7	58.1	57.5	57.6	57.9	57.6	57.7		
95	59.3	59.9	60.6	60.8	60.9	60.7	60.5	60.2	60.1	59.9	59.1	58.3	58.1	58.2	58.0	58.0	58.0		
100	59.1	59.5	60.0	60.2	60.2	60.1	60.0	60.1	60.3	60.2	59.7	58.9	57.9	57.5	57.2	57.1	57.1		
105	58.3	58.5	58.7	58.7	58.6	58.5	58.5	58.7	58.7	58.5	57.8	57.0	56.0	55.4	54.8	54.6	54.6		
110	57.0	56.9	56.8	56.7	56.5	56.5	56.4	56.4	56.2	55.8	54.9	53.9	52.9	52.2	51.5	51.3	51.3		
115	55.3	55.2	54.9	54.7	54.4	54.4	54.1	53.9	53.6	53.2	52.1	51.0	49.9	49.0	48.0	47.9	47.8		
120	53.3	53.2	52.8	52.6	52.3	52.1	51.8	51.6	51.3	50.8	49.7	48.6	47.3	46.3	45.3	45.1	45.0		
125	50.9	50.8	50.4	50.2	49.8	49.7	49.3	49.1	48.6	48.0	46.8	45.8	44.6	43.7	42.7	42.4	42.3		
130	47.9	47.8	47.5	47.2	46.8	46.7	46.2	46.0	45.4	44.7	43.3	42.2	41.1	40.5	39.7	39.4	39.3		
135	44.2	44.1	43.8	43.6	43.2	43.1	42.5	42.2	41.5	40.8	39.6	38.5	37.3	36.6	35.9	35.6	35.4		
140	39.4	39.4	39.0	38.8	38.4	38.3	37.7	37.3	36.7	36.3	35.3	34.3	32.9	32.0	31.2	30.9	30.6		
145	33.8	33.9	33.5	33.4	33.0	32.9	32.2	31.9	31.3	30.9	29.9	29.1	28.0	27.2	26.3	26.0	25.7		
150	27.9	28.0	27.7	27.6	27.2	27.1	26.5	26.1	25.4	24.8	23.8	23.3	22.4	21.9	21.3	21.1	20.7		
155	21.6	21.8	21.5	21.5	21.1	21.1	20.4	20.0	19.2	18.7	17.8	17.4	16.7	16.4	15.9	15.8	15.5		
160	15.1	15.4	15.1	15.2	14.9	14.8	14.3	14.0	13.4	13.1	12.4	12.1	11.5	11.3	10.9	10.9	10.6		
165	9.16	9.35	9.19	9.29	9.05	9.06	8.71	8.60	8.21	8.02	7.59	7.42	7.00	6.89	6.58	6.60	6.39		
170	4.16	4.33	4.22	4.39	4.25	4.35	4.18	4.22	3.99	3.96	3.69	3.64	3.40	3.36	3.19	3.22	3.12		
175	1.42	1.45	1.45	1.48	1.47	1.50	1.50	1.52	1.50	1.48	1.44	1.39	1.36	1.33	1.32	1.32	1.33		
180	0.73	0.73	0.72	0.72	0.72	0.72	0.71	0.71	0.72	0.71	0.71	0.71	0.71	0.71	0.72	0.71	0.75		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:20DEG
Operators:JOE
Test Date:2021-09-09

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.366
Humidity:45%
Test Distance:8.040m [K=1.0000]
Remarks: